IN THE CLAIMS

Please amend claim 1 as follows:

Claim 1 (Currently Amended): A sliding bearing wherein comprising an overlay, which

consists consisting of at least one solid lubricant and a binder resin, said overlay covers an

aluminum-alloy bearing layer bonded on backing metal, and characterized in that said overlay

consists of an upper layer comprising said layer, which contains the solid lubricant essentially

consisting essentially of MoS₂, and a lower layer, which consists consisting of one or both of at least

one solid lubricant and at least one hard additive, (when wherein when said the solid lubricant of the

said lower layer is MoS₂, its content is relatively lower than that of the said upper layer layer layer).

Claim 2 (Original): A sliding bearing according to claim 1, wherein the MoS₂ content of the

upper layer is from 40 to 95 mass %.

Claim 3 (Original): A sliding bearing according to claim 2, wherein the content of the solid

lubricant and hard additive of said lower layer is from 30 to 85 mass %.

Claim 4 (Original): A sliding bearing according to claim 3, wherein said lower layer

contains only the solid lubricant.

-2-

U.S. Patent Application Serial No. 10/088,487 Response dated April 6, 2004 Reply to OA of January 12, 2004

Claim 5 (Original): A sliding bearing according to claim 4, wherein said solid lubricant is MoS₂.

Claim 6 (Original): A sliding bearing according to claim 5, wherein the MoS₂ content of said upper layer is more than the MoS₂ content of said lower layer by 10 mass % or more.

Claim 7 (Original): A sliding bearing according to any one of claims 1 through 6, wherein the hard additive of said lower layer is at least one selected from the group consisting of Si_2N_4 , SiO_2 , SiC and Al_2O_3 .

Claim 8 (Previously Presented): A sliding bearing according to any one of claims 1 through 6, wherein said upper layer consists of two or more sub-layers having different MoS₂ content of the upper sub-layer is more than the MoS₂ content of the lower sub-layer.

Claim 9 (Previously Presented): A sliding bearing according to any one of claims 1 through 6, wherein said lower layer consists of two or more sub-layers having different additive amount.